



## High-resolution color display and self-labeling keys

D717

### Key Features

- High-resolution color display
- 3 configurable self-labeling multicolor LED keys
- Wideband audio
- USB port
- Elegant design
- 3-year standard warranty

The D717 SIP Color Deskset features an intuitive design with advanced technology and connectivity. Three self-labeling programmable feature keys sit next to a 2.8-inch, 320 x 240 pixel color LCD display. Opus codec support gives you the freedom to enjoy crystal-clear audio or high-quality narrowband audio, depending on your network conditions. Zero touch provisioning eliminates the need for manual labor typically involved with installation. Power over Ethernet (PoE) support and dual Ethernet ports makes the system cost-effective and easy to use. The USB port allows additional connectivity, including up to three D7 expansion modules for increased visibility and one-button options. The system features multiple configurations, including three programmable feature keys, four soft keys and 14 dedicated feature keys. You'll feel safe with powerful security features like VPN support.

### Product Highlights

- High-resolution 2.7" graphical TFT display
- 3 self-labeling function keys
- Wideband hands-free talking (speakerphone)
- Digital Signal Processor (DSP) enhanced audio quality
- 2-port Gigabit Ethernet switch (RJ45)
- Power over Ethernet IEEE 802.3af, Class 2
- USB headset<sup>(1)</sup> ready
- D7 Expansion Module<sup>(1)</sup> ready
- Support for USB WiFi stick
- Electronic Hook Switch (EHS)<sup>(1)</sup> support for wireless headsets
- Dual-angle footstand: 46° and 28°

## Phone Features

- 6 SIP identities / accounts
- XML browser
- Call lists for dialed, received, missed calls
- Local directory with 1000 entries
- Multiple language support
- DTMF in-band / out-of-band / SIP-INFO
- Interoperable with all major IP PBX platforms
- Speed dialing
- URL dialing
- Local dial plan
- Automatic redial on busy
- Call completion (busy/unreachable)<sup>[2]</sup>
- Caller identification
- Call waiting
- Call blocking (deny list)
- Auto answer
- Hold
- Music on hold<sup>[2]</sup>
- Blind and attended transfer
- Call forwarding
- 3-way conferencing on the phone
- Extension monitoring, call pickup<sup>[2]</sup>
- Call park, call unpark<sup>[2]</sup>
- Multicast paging
- DND mode (do not disturb)
- Keyboard lock
- Client matter code (CMC)<sup>[2]</sup>
- Unified Communications ready

### Audio

- Codecs:
  - G.711 A-law,  $\mu$ -law
  - G.722 (wideband)
  - G.726, G.729AB, GSM 6.10 (FR)
- Built-in assignable ringtones
- Comfort noise generator (CNG)
- Voice activity detection (VAD)

### Setup

- Configurable through web interface
- Provisioning:
  - Automatic loading of settings via HTTP/HTTPS/TFTP
  - DHCP Options 66/67
  - Snom Redirection Service
  - Remote management via TR-069 / TR-111

## Specifications

### Protocols

- SIP (RFC3261)
- DHCP, NTP
- HTTP / HTTPS / TFTP
- LDAP (Directory)
- Dual Stack IPv4 / IPv6

### User Interface

- Localization (language, time, dial tone)
- Red LED for call indication / message waiting
- 4 context sensitive keys
- 3 programmable line / function keys with multicolour LEDs
- Dedicated keys for: Message, DND, directory, menu, transfer, hold, page
- Audio keys with LED indication: Mute, speakerphone, headset
- Volume key
- 5-way navigation key
- OK and cancel keys
- Sensor-assisted user interface

### Security

- 802.1X Authentication and EAPOL
- Transport layer security (TLS)
- SRTP (RFC3711), SIPS, RTCP
- HTTPS server/client
- Password-protected web interface
- VPN support
- VLAN (IEEE 802.1Q)
- LLDP-MED, RTCP-XR

### Specifications, Weights and Dimensions

- Dimensions (approx.):
  - 7.28" x 3.54" x 8.66"
  - With desk stand: "7.28" x 8.46" x 6.81"
- Weight (approx.): 1.8 lbs
- Input voltage: 5V DC (SELV)
- Power supply: PoE or 5Vdc power adapter<sup>[1]</sup>, 10 Watts
- Handset: 4P4C
- Headset: 4P4C; Support for Snom EHS Advanced<sup>[1]</sup>
- Hearing aid compatible (HAC) handset
- 1 x USB 2.0 host port, Type A

- Environmental conditions:
  - Ambient temperature: 0°C to 35°C (32°F to 95°F)
  - Storage temperature: -10°C to 45°C (14°F to 113°F)
  - Humidity: 5% to 95% (non-condensing)
- Included in delivery:
  - Phone unit
  - Foot stand
  - Handset with cord
  - Ethernet cable
  - Quick Start Guide
- Color: Black
- Warranty: 3 years
- Part Number: 00004397 (all markets)
- APN: 80-S065-00

<sup>[1]</sup> Optional accessory

<sup>[2]</sup> If supported by PBX

### APN numbers for optional accessories

80-S007-00	D7 Expansion Module (black)
26-350200-3UL	Power Adapter Snom A6 /US clip
89-S015-00	Snom EHS Advanced
00-S013-00	Wallmount plate for 7-series
89-4083-00	A100D Binaural headset
89-4082-00	A100M Mono headset
80-S058-00	A210 Wi-Fi USB Dongle
80-S050-00	A230 DECT USB Dongle
80-S094-00	A171 DECT Headset