

BLUESOCKET 1930/1935 High-Performance Dual Radio 802.11n Access Point

PRODUCT FEATURES

- 802.11a/b/g/n wireless access points supporting MIMO antenna technology
- Dual radio 2.4 GHz and 5 GHz
- Full 3x3:3 MIMO performance, offering data rates up to 450 Mbps per radio
- Fully functional with 802.3af Power over Ethernet (PoE)
- Mesh Networking
- User configurable maximumassociated clients per radio
- "Zero-touch" AP deployment– APs automatically discover vWLAN, and download firmware and configurations
- Layer 7 Device Fingerprinting provides reporting and analytics of device types and device-specific policies
- Supports WMM/802.11e and QoS for Enterprise-class Voice over Wi-Fi
- DynamicRF Radio Resource Management Technology– automatically configures optimal radio settings to maximize performance
- Integrated wireless intrusion detection system to identify rogue access points and wireless attacks
- Supports stateful firewall for highest security at the edge
- Provides greater range through beamforming



ADTRAN's wireless portfolio includes a family of 802.11n and 802.11ac high-performance Access Points (APs) that are a perfect fit for enterprises of all sizes, including educational institutions, retail, hospitality, and healthcare providers who are looking to move their organizations to a pervasive mobility environment. Bluesocket* APs are completely plugand-play requiring no manual configuration and deliver optimal performance. Whether you want to add wireless to your office or deploy across an entire campus, the Bluesocket APs are designed to meet your needs.

High-Performance, Reliable Connectivity

The Bluesocket 1930 and 1935 indoor APs offer enterprise-grade performance, with three transmit and three receive streams providing data rates up to 450 Mbps per radio for a total of 900 Mbps per AP. The Bluesocket 1930 AP includes six MIMO internal antennas with up to 4dBi peak gain, and the Bluesocket 1935 includes six RP-SMA connectors for external antennas.

The Bluesocket 1930 and 1935 APs provide high performance, reliable coverage in ultra-high density wireless environments, such as indoor arenas, conference centers, libraries, and other high traffic areas. The Bluesocket 1930s Series APs support the newer generation of laptops with three stream radio support, and offer higher receive sensitivity on both the 2.4 Ghz and 5 Ghz radios to compensate for Bring Your Own Device (BYOD) type mobile devices such as smartphones and tablets that have a fraction of the transmit power of traditional laptops.

The Bluesocket 1930 and 1935 APs are fully functional with the power delivered by a single-port 802.3af PoE solution.

Flexible, Cloud-Managed Options

The Bluesocket APs operate in conjunction with ADTRAN's flexible portfolio of cloud-managed deployment options including public cloud, private cloud or partner cloud with the freedom to migrate among them.

ADTRAN's wireless solutions are built on Bluesocket virtual Wireless LAN (vWLAN), the industry's premier cloud-managed wireless LAN. vWLAN[®] is simple yet powerful: simple in that it is intuitive, easy to learn, setup and use, and powerful with unmatched visibility, security, reliability, scalability and performance. In addition, ADTRAN's ProServicesSM offer the most robust lifecycle professional services—from initial designs, to onsite surveys, to installations, all the way to end-user Help Desk.

Deployments Made Simple—Auto Provision, Auto Configure, Auto Optimize

- Zero-touch AP Deployment: APs automatically discover vWLAN in the cloud, download firmware and download configuration.
- Zero-IT Setup: Enjoy a fully functional employee and guest network in minutes with just a few clicks and keystrokes.
- **DynamicRF:** Radio Resource Management (RRM) technology maximizes performance, adapts to interference, and provides seamless L2/L3 mobility by automatically setting channel and TX power settings, discovering neighbors and load balancing.

Unmatched Visibility and Insight

Cloud management allows you to view, manage and optimize the Wi-Fi^{*} network from any device—anytime.

- Customizable Reporting and Analytics Dashboards provide realtime and historical business insight into the network.
- Multi-tenant Support enables centralized management of multiple customers or business entities from a single software instance.

Unsurpassed Security, Reliability, Scalability and Performance

- Context-aware Access Control (with Layer 7 Device Fingerprinting) allows for defining security policies based on users, device type, ownership, location and schedules. Businesses can now support BYOD or allow guest access while ensuring highest levels of network security.
- Built-in Wireless Intrusion Detection (W-IDS) to detect and isolate rogue access points in the network.
- Built-in High-Availability (HA) with zero packet loss failover ensures a reliable, always-on network.
- Elastic Scalability allows the network to quickly scale without the constraints of legacy hardware controllers.

PRODUCT SPECIFICATIONS

Interfaces

One Auto-sensing, 10/100/1000Base-T, Serial Console Port, RJ-45 Connector

Antenna

- Bluesocket 1930: Six Internal MIMO Antennas with 4dBi Gain
- Bluesocket 1935: Six External RP-SMA Connectors

Radios

- 802.11a/n and 802.11b/g/n
- Configurable for Sensor-mode RF Scanning
 DynamicRF (Radio Resource Management) for Automatic Channel, TX Power and
- Neighbor Discovery
 Configurable Maximum Associated Clients per Radio
- Multicast/Broadcast to Unicast Conversion
- A-MPDU and A-MSDU Frame Aggregation
- HT20 and HT40 High Throughput
- Max Aggregate TX Power
 - 2.4 Ghz: 24 dBm/1250 mW
 - 5 Ghz: 20 dBm/100 mW
- Beamforming

Certifications

Wi-Fi 802.11a/b/g/n Certification

*Aggregate of chains. May be limited by local regulatory domains (country) and band edge requirements.

Mobility Services

- Eight SSIDs Per Radio
- Support for Apple Bonjour-based Services (Airprint, Airplay), Apple CNA, and Microsoft NCSI
- Wireless Client Load Balancing
- Secure Fast Roaming with Opportunistic Key Caching (OKC)
- Seamless Layer 2 and Layer 3 Roaming
- High Availability
- Mesh Networking

QoS for Voice, Data, and Video

- Smart Bandwidth Management (Incoming, Outgoing)
- WMM (802.11e)
- 802.1p or Differentiated Service Code Point (DSCP)
- WMM Power Save (U-APSD)

Security

- 802.1X Port-based Authentication
- Open System (WEP-64/128)
- Shared System (WEP-64/128)
- WPA/WPA2-Personal
- WPA/WPA2-Enterprise
- EAP-TTLS
- EAP-PEAP
- EAP-FAST
- EAP-TLS
- EAP-SIM
- EAP-AKA

Environment

- Operating: 32° F to 122° F (0° C to 50° C)
- Storage: -40° F to 158° F (-40° C to 70° C)
- Humidity: 5% to 90% Typical

Physical

Bluesocket 1930 AP

- Dimensions: 6.5 in. x 6.5 in. x 1.5 in. (W x D x H) (165 mm x 165 mm x 35 mm)
- Weight: 1.25 lbs (0.6 kg)

Bluesocket 1935 AP

- Dimensions: 6.5 in. x 6.5 in. x 1.5 in. (W x D x H) (165 mm x 165 mm x 35 mm)
- Weight: 1.25 lbs (0.6 kg)

Power

- 802.3af Compliant Power over Ethernet
- External 12V DC Power Adapter (Optional)

Mounting

- Wall/Ceiling/T-bar Mount Kit Included
- Plenum Rated
- Anti-Theft: Compatible with Kensington-style Locks

Agency Approvals

Electrical/Safety Compliance

- UL 1950
- CSA 22.2
- IEC 60950
- EN 60950

Radio Approvals

- FCC Part 15.247
- RSS-210 (Canada)
- EN 300.328 (Europe)
- AS/NZS 4771 (Australia & New Zealand)
- NCC (Taiwan) and IDA (Singapore)
- EMI and Susceptibility (Class A)
- FCC Part 15.107 and 15.109
- ICES-003 (Canada)
- EN 301.489-1 and -17 (Europe)
- AS/NZS 3548


Warranty

Limited Lifetime Warranty




ANTENNA PATTERNS

BSAP 1930 - 2.4 GHz




Horizontal or Azimuth (Top View)




Elevation (Side View)

ANTENNA PATTERNS

BSAP 1930 – 5 GHz



Horizontal or Azimuth (Top View)



Elevation (Side View)



POWER AND SENSITIVITY TABLE

	Max TX Power*		Receive Sensitivity*
802.11b 2.4 GHz			
1~2 Mbps	24 dBm	1 Mbps	-93 dBm
5.5~11 Mbps	23 dBm	11 Mbps	-90 dBm
802.11g 2.4 GHz			
6~24 Mbps	23 dBm	6 Mbps	-92 dBm
36 Mbps	22 dBm		
48 Mbps	21 dBm		
54 Mbps	20 dBm	54 Mbps	-76 dBm
802.11n 2.4 GHz HT20			
MCS0/MCS8/MCS16	22 dBm	MCS0/8/16	-90 dBm
MCS1/MCS9/MCS17	21 dBm		
MCS2/MCS10/MCS18	21 dBm		
MCS3/MCS11/MCS19	21 dBm		
MCS4/MCS12/MCS20	20 dBm		
MCS5/MCS13/MCS21	20 dBm		
MCS6/MCS14/MCS22	19 dBm		
MCS7/MCS15/MCS23	19 dBm	MCS7/15/23	-73 dBm
802.11n 2.4 GHz HT40			
MCS0/MCS8/MCS16	21 dBm	MCS0/8/16	-88 dBm
MCS1/MCS9/MCS17	20 dBm		
MCS2/MCS10/MCS18	20 dBm		
MCS3/MCS11/MCS19	20 dBm		
MCS4/MCS12/MCS20	19 dBm		
MCS5/MCS13/MCS21	19 dBm		
MCS6/MCS14/MCS22	18 dBm		
MCS7/MCS15/MCS23	18 dBm	MCS7/15/23	-70 dBm

*Aggregate of chains. May be limited by local regulatory domains (country) and band edge requirements.

POWER AND SENSITIVITY TABLE

	Max TX Power*		Receive Sensitivity*
802.11a 5 GHz			
6~24 Mbps	20 dBm	6 Mbps	-90 dBm
36 Mbps	17 dBm		
48 Mbps	15 dBm		
54 Mbps	13 dBm	54 Mbps	-77 dBm
802.11n 5 GHz HT20			
MCS0/MCS8/MCS16	18 dBm	MCS0/8/16	-88 dBm
MCS1/MCS9/MCS17	17 dBm		
MCS2/MCS10/MCS18	17 dBm		
MCS3/MCS11/MCS19	17 dBm		
MCS4/MCS12/MCS20	15 dBm		
MCS5/MCS13/MCS21	14 dBm		
MCS6/MCS14/MCS22	13 dBm		
MCS7/MCS15/MCS23	13 dBm	MCS7/15/23	-76 dBm
802.11n 5 GHz HT40			
MCS0/MCS8/MCS16	17 dBm	MCS0/8/16	-86 dBm
MCS1/MCS9/MCS17	16 dBm		
MCS2/MCS10/MCS18	16 dBm		
MCS3/MCS11/MCS19	16 dBm		
MCS4/MCS12/MCS20	14 dBm		
MCS5/MCS13/MCS21	14 dBm		
MCS6/MCS14/MCS22	13 dBm		
MCS7/MCS15/MCS23	13 dBm	MCS7/15/23	-72 dBm

*Aggregate of chains. May be limited by local regulatory domains (country) and band edge requirements.



Bluesocket 1930/1935

High-Performance Dual Radio 802.11n Access Point

ORDERING INFORMATION

Choose Your Access Point

~

.

...

~

Choose Your AP	Part Number
Indoor APs	
Bluesocket 1930: 802.11a/b/g/n, 3x3:3, six internal MIMO antennas	1700950F1
Bluesocket 1935: 802.11 a/b/g/n, 3x3:3, six external RP-SMA connectors	1700951F1

Choose Your Cloud			
Public Cloud – ProCloud	Part Number	Part Number	
ProCloud for Indoor AP	NBD	7x24x4	
One Year	1100MSPH200112	1100MSPH300112	
Three Years	1100MSPH200136	1100MSPH300136	
Five Years	1100MSPH200160	1100MSPH300160	
Public Cloud – ProCloud Plus	Part Number	Part Number	
ProCloud Plus for Indoor AP	NBD	7x24x4	
One Year	1100MSPM200112	1100MSPM300112	
Three Years	1100MSPM200136	1100MSPM300136	
Five Years	1100MSPM200160	1100MSPM300160	
Private Cloud		Part Number	
FREE vWLAN Virtual Appliance (VMware) (\$1995 value)	(www.ao	Download Only (www.adtran.com/downloadvwlan)	
vWLAN 1U Rackmount Appliance (Hardware)		1700900F2	
vWLAN Desktop Appliance (Hardware)		1700918F1	

Licenses

Software License	Part Number
FREE Access Point vWLAN Software License (\$235 value)	1951901G1
Access Point Unified User Access (Wired and Third-Party AP Support) Software License (Optional)	1951910G1

Accessories

Power Supply and Antennas	Part Number
802.3af Compliant PoE Injector for BSAP 1930/1935	1700926F1
AC/DC Power Adapter for BSAP 1930/1935	1700929F1
Antenna Bundle for BSAP 1930/1935	1700931F1

ADTRAN, Inc. 901 Explorer Boulevard Huntsville, AL 35806 P.O. Box 140000 Huntsville, AL 35814-4000

256 963-8000 256 963-8699 fax

General Information 800 9ADTRAN info@adtran.com www.adtran.com

International **Customer Service** +1 256 963 8716

Pre-Sales Technical Support 888 423-8726 application.engineer@adtran.com www.adtran.com/presales

Post-Sales Technical Support 888 423-8726 support@adtran.com www.adtran.com/supportcase

Where to Buy 888 423-8726 www.adtran.com/where2buy

Training 888 423-8726 training@adtran.com

Canada Headquarters-Toronto, Ontario +1 877 923 8726 +1 905 625 2515 sales.canada@adtran.com

Canada-Montreal, Quebec +1 877 923 8726 +1 514 940 2888 sales.canada@adtran.com

Mexico and Central America +1 256 963 3321

+1 52 55 5280 0265 Mexico sales.cala@adtran.com South America

+1 256 963 3185 sales.brazil@adtran.com sales.latam@adtran.com

61700950F1-8J

December Copyright © 2015 ADTRAN, Inc. All rights reserved, ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. ADTRAN, Bluescoket and vWLAN are registered trademarks of ADTRAN, Inc. and its affiliates in various countries. All other trademarks mentioned in this document are the property of their respective owners.

ADTRAN warranty duration and entitlements vary by product and geography. For specific warranty information, visit www.adtran.com/warranty

ADTRAN products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding ADTRAN's export license, please visit www.adtran.com/exportlicense



TL9000

