

NetVanta

3148

Fixed-Port Secure Access Ethernet Router



Gigabit



Ready



VQM



VoIP

Benefits

- Managed router with four Gigabit Ethernet interfaces and 8-port PoE switch
- PoE option includes 200W PoE budget
- Voice Quality Monitoring (VQM) and Mean Opinion Score (MOS) prediction
- Utilizes standards-based routing protocols utilized by the widely deployed NetVanta Series
- Compatible with industry-leading soft-switches and call agents
- Dynamic bandwidth allocation affords more efficient utilization
- Stateful inspection firewall for network security
- Quality of Service (QoS) for delay and jitter sensitive traffic like VoIP
- Supports 802.1q Virtual LAN (VLAN) Trunking
- Command Line Interface (CLI) mimics industry de facto standard
- Network Address Translation (NAT) for IP address concealment
- Feature-rich ADTRAN® Operating System (AOS)
- Industry-leading, North American five-year warranty
- Optional IPSec Virtual Private Network (VPN) for secure tunneling
- Optional full-featured eSBC for robust network security and voice interoperability

Overview

The NetVanta® 3148 is a fixed-port, high-performance Ethernet router supporting converged access and high-quality voice services. It provides four routed, autosensing Gigabit interfaces, two of which can be fiber fed, and an 8-port PoE ethernet switch. This product is ideal for carrier bundled service offerings up to 500Mbps, and enterprise-class Internet access for secure, high-speed corporate connectivity. The NetVanta 3148 is available as a 1U-high rack-mountable platform.

Flexibility and Redundancy

The NetVanta 3148 is ideal for multiple applications where Ethernet redundancy is needed given the four Gigabit ports that can be either LAN or WAN facing. This can be achieved with two Ethernet delivered access services providing immediate failover to the active link anytime a link down event occurs. Many deployments still feature separate voice and data networks, and the NetVanta 3148 is a perfect fit for these as well with a single WAN link, using the other Gigabit interfaces to accomplish this.

Standards Protocols

The versatile hardware platform of the NetVanta 3148 is further complemented with the ADTRAN Operating System (AOS). The AOS allows for the support of static and default routes, demand and policy-based routing, and allows for fast, accurate network convergence using routing protocols such as BGP, OSPF, RIP, and PIM Sparse Mode for multicast routing. Multihoming is also available to provide redundant or backup WAN links to multiple ISPs, guaranteeing a wide area connection.

Hierarchical QoS

QoS is also supported for delay-sensitive traffic like VoIP or video. To prioritize mission-critical traffic and control network congestion, the NetVanta 3148 uses Low Latency Queuing, Weighted Fair Queuing (WFQ), Class-based WFQ, and DiffServ marking to establish the priority of IP packets routed over the WAN.

VoIP Ready

The NetVanta 3148 is VoIP-ready with Quality of Service (QoS), Class of Service (CoS), Session Initiation Protocol (SIP) Transparent Proxy, Net Flow 9 Traffic Monitoring, and Voice Quality Monitoring (VQM). Traffic Monitoring is for collecting and measuring network traffic patterns, while VQM is a graphically intuitive interface displaying captured data for Mean Opinion Score (MOS), jitter, delay, and packet loss statistics necessary to troubleshoot VoIP calls.

The NetVanta 3148 also deploys VQM to capture MOS, jitter, delay, and packet loss statistics necessary to troubleshoot VoIP calls over the WAN. This powerful, yet graphically intuitive, diagnostic tool allows for quick isolation of network issues to ensure superior call quality.

NETVANTA 3148

Enterprise Session Border Control (eSBC)

The NetVanta 3148 can provide optional eSBC functionality delivering a truly converged application platform at the customer premises. This feature is becoming mandatory in today's service deployments to normalize, secure and troubleshoot the SIP-to-SIP communication between a carrier network and the customer's SIP-compliant equipment. The strength of the NetVanta 3148 is its ability to grow as your VoIP services expand, supporting up to 300 calls.

Security

The AOS provides a powerful, high-performance stateful inspection firewall. The firewall can identify and protect against common Denial of Service (DoS) attacks like TCP syn flooding, IP spoofing, ICMP redirect, ping-of-death, and IP reassembly problems.

In addition, the AOS is capable of providing an inherent URL-filtering package without the use of an external server. URL filtering is another level of security that allows system administrators to restrict Internet access by permitting or denying specific URLs. This URL filtering feature also includes the ability to produce top website reports of the most frequently requested websites, allowing system administrators to modify the URL filter lists.

PoE

The eight-port switch in the NetVanta 3148P provides up to 200 watts of 802.3af (PoE), 802.3at (PoE+) and Legacy PoE for powering IP phones, WAPs, and other devices requiring LAN power.

The NetVanta 3148 also adds the support for IPSec-compliant VPN. The NetVanta 3148 supports encryption algorithms like DES, 3DES, and AES. With this upgrade, the NetVanta 3148 is fully compatible with other IPSec VPN equipped NetVanta products.

Management

The NetVanta 3148 can be remotely managed by ADTRAN's n-Command® MSP platform. ADTRAN n-Command platforms offer the ability to discover devices, make mass configuration changes or firmware upgrades, backup/restore configuration, and generate inventory reports for asset management. ADTRAN n-Command MSP also offers VoIP VQM and reporting, as well as an industry-leading, easy-to-use, Graphical User Interface (GUI). NetVanta 3148 is rack mountable and backed by an industry-leading warranty.

Administration

The AOS offers an intuitive Web-based GUI that provides step-by-step configuration wizards, management capability, and the ability to upload firmware updates. In addition, it has a standard CLI that mimics the widely adopted, industry de facto standard. The sequence of commands required to configure similar devices is almost identical, eliminating training costs typically associated with learning a new operating system or obtaining costly industry certifications. The CLI also allows for configuration scripts to be used, saved, and downloaded as a quick-and-easy recovery mechanism.



Product Specifications

Physical Interfaces

- 2 – 1.0/2.5 Gbps SFP Ports
- 2 – 1.0 Gigabit Ethernet Interfaces
- 8 – 10/100/1000Base-T PoE Ethernet Switch
- Full Duplex
- Auto-negotiation
- RJ-45
- USB 2.0
- Console Port

Status LEDs

- Status (Power)
- USB
- PoE (NetVanta 3148P only)
- Gigabit ports 1 - 4
- Ethernet Switch 1 - 8

Throughput

- Routing/NAT/FW: 1Mpps
- VPN iMIX: 150Mbps

Quality of Service (QoS)

- Low Latency and Weighted Fair Queuing (WFQ)
- Class-Based WFQ
- DiffServ Packet Marking and Recognition
- Traffic Monitoring (NetFlow 9)

Voice Quality Monitoring (VQM)

- Mean Opinion Score (MOS) Prediction
- Jitter, Delay and Packet Loss
- Past and Active Calls

Fixed-Port Secure Access Ethernet Router

Traffic and Network Quality Monitoring

- ICMP and TWAMP Probes and Tracks
- One-Way Delay
- Round-Trip Loss and Delay
- Inter-Packet Delay Variance
- Traffic Flow Collection and Analysis
- Packet Capture

Administration

- Familiar Command Line Interface (CLI)
- Web-Based GUI
- n-Command Support
- SNMP V2 and V3
- SYSLOG Logging
- Email Alerts (SMTP)
- Policy Statistics
- TCL Scripting
- Login Privilege Levels
- Telnet, Craft/Console Port, SSH, Ping,
- Trace Route and NTP

DHCP

- Client, Server and Relay

Firewall

- Stateful Inspection Firewall
- Denial of Service (DOS) Protection
- Access Control Lists
- Application Level Gateways
- Packet Filtering

Protocols

- EBGp/iBGP
- RIP (v1 and V2)
- PIM Sparse Mode
- IGMP V2
- GRE
- PPP Dial Backup
- PAP and CHAP
- Multi-VRF CE
- TWAMP
- OSPF
- PPPoE
- Multilink PPPoE
- Demand Routing
- RFC 1483
- Multihoming
- Layer 3 Backup
- VRRP

Network Address Translation

- Basic NAT (1:1), NAT (Many:1) and 1:1 Port Translation

NAT Traversal and Remote Survivability

- B2BUA
- SIP Registrar for IP Phones
- SIP Proxy with Survivability
- Transparent/Stateful/Outbound

Content Filtering

- Inherent URL Filtering
- Top Website Reports
- Integration with Websense

Secure Management

- Multilevel Access Control
- TACACS+
- RADIUS AAA
- SSH CLI and SSL GUI
- Port Authentication (802.1x)

PoE (NetVanta 3148P only)

- 802.3at
- 802.3af
- 200W PoE Budget

VPN (Optional)

- IPSec Tunnel Mode: 500 Tunnels
- Encryption: DES, 3DES and AES
- Authentication Mechanisms: XAUTH, Digital Certificates, Pre-shared Keys and Secure ID

Environment

- Operating Temperature: 32° to 122° F (0° to 50° C)
- Storage Temperature: -40° to 158° F (-20° to 70° C)
- Relative Humidity: Up to 95%, Non-condensing

Physical and Power

- 1U Metal Rackmount
- Dimensions: 1.72 in. x 8.4 in. x 8 in. (H x W x D), (4.36 cm x 21.3 cm x 20.3 cm)
- Weight: 3 lbs. (1.4 kg)
- Power: AC (Auto-ranging, 100 to 250 VAC, 50/60 Hz, 0.4 A Maximum)

Agency Approvals

- FCC Part 15 Class A
- CE Mark
- UL & Canadian UL
- RoHS
- C-Tick for Australia and New Zealand

NETVANTA 3148

Ordering Information

Equipment	Part No.
NetVanta 3148	17003148F1
NetVanta 3148 with EFP (VPN and VQM)	47003148F2
NetVanta 3148 25-Session SBC	47003148F2#25
NetVanta 3148 50-Session SBC	47003148F2#50
NetVanta 3148 100-Session SBC	47003148F2#100
NetVanta 3148 300-Session SBC	47003148F2#300
NetVanta 3148P	17003148F11
NetVanta 3148P with EFP (VPN and VQM)	47003148F21
NetVanta 3148P 25-Session SBC	47003148F21#25
NetVanta 3148P 50-Session SBC	47003148F21#50
NetVanta 3148P 100-Session SBC	47003148F21#100
NetVanta 3148P 300-Session SBC	47003148F21#300
Software Options	Part No.
NetVanta 3148 EFP Upgrade	19503148F2
NetVanta 3148 SBC Upgrade, 5 Calls	1963SBCF5
NetVanta 3148 SBC Upgrade, 10 Calls	1963SBCF10
NetVanta 3148 SBC Upgrade, 25 Calls	1963SBCF25
NetVanta 3148 SBC Upgrade, 50 Calls	1963SBCF50
NetVanta 3148 SBC Upgrade, 100 Calls	1963SBCF100
NetVanta 3148 SBC Upgrade, 300 Calls	1963SBCF300



ADTRAN, Inc.
901 Explorer Boulevard
Huntsville, AL 35806
256 963 8000

General Information
800 9ADTRAN
adtran.com/contactus

Canada—Montreal, Quebec
+1 877 923 8726
+1 514 940 2888
sales.canada@adtran.com

Mexico and Central America
+1 52 55 5280 0265 Mexico
sales.cala@adtran.com

617003148F1-8B

August Copyright © 2021 ADTRAN, Inc. All rights reserved. ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. ADTRAN and the other trademarks listed at www.adtran.com/trademarks are registered trademarks of ADTRAN, Inc. or its affiliates in various countries. All other trademarks mentioned in this document are the property of their respective owners.

ADTRAN warranty duration and entitlements vary by product and geography. For specific warranty information, visit www.adtran.com/warranty

ADTRAN products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding exportation of ADTRAN items (e.g. commodities, technology, software), please visit www.adtran.com/exportlicense.



ISO 9001
ISO 14001
TL 9000