

CXR2000 CompletePBX Telephony System for SMB

The CXR2000 is an Intel Atom® based stand-alone telephony solution with PSTN / telephone ports.

The CXR2000 features Xorcom CompletePBX 5 management interface, with up to 32 analog

ports, up to eight BRI ISDN ports, and/or a single PRI/R2/CAS ISDN E1/T1 port. The CXR2000 supports up to 160 PSTN / Analog phones ports with external Astribank units, up to 200 users and up to 85 concurrent calls.



Features

- Unlimited voicemail boxes, hunt groups, call center groups, and auto attendants (IVRs)
- Basic built-in call center with call recording, barge and whisper
- Hot-desking
- Sophisticated Classes of Service for enhanced security
- Emergency notification module
- Endpoint manager
- User-friendly Web interface
- Interface in different languages
- CDR (Call Details Record)
- TDM/SIP/IAX trunks
- Remote extensions
- Voicemail
- Voicemail to email
- Web access to voicemail
- Fax support
- Fax to email
- IVR menu system
- Ring groups
- Call queues
- Conference rooms
- Follow me
- Time-based routing
- Advanced dialing rules
- Music-on-hold
- Paging and intercom
- Admin status screen
- Package manager (for easy updates)
- Network settings tool

Software

Software version	Xorcom CompletePBX 5 (64-bit)
Linux version	CentOS 7
Framework	Asterisk 18
Security	Intrusion protection software, firewall protection


Hardware

Processor	Intel Celeron N3060 Dual Core 1.6 GHz
RAM	2 GB
Storage	250 GB SSD/500 GB SSD
Echo Cancellation Module	Voice enhancement & echo cancellation (optional)
USB	4

Telephony

Maximum number of concurrent calls	85 (SIP only); 45 (PRI + FXS)
Maximum number of built-in analog ports	32 (additional ports with external Astribank units)
Number of E1 / T1 ports	1 (up to 30 concurrent PRI/R2/CAS calls)
Maximum telephony modules supported internally	4 (additional Astribank ports are supported by adding Astribank units)
Maximum number of telephony ports supported internally	54 (E1 PRI/R2/CAS + 24 analog ports)
Supported Xorcom telephony modules	<ul style="list-style-type: none"> • 8 FXS ports • 8 FXO ports • 1 PRI/R2/CAS port • Up to 8 BRI ISDN ports

Power

Power supply	Internal
Voltage	Switching, auto adjust 100/240 Volts, 50/60 Hz
Power consumption	230 Watts (maximum)
Built in grounding connection	

Network

Ethernet port	10/100/1000 Mb/s
---------------	------------------

Maintenance and Support

- Monitor and keyboard support
- Rapid Recovery™ backup utility provided on Disk-on-Key
- Internet updates

Environment

Storage temperature	-20° to 70° Celsius (-4° -158° F)
Working temperature	0° to 40° Celsius (32° -104° F)
Humidity	20%-95%, non-condensing

Dimensions and Weight

Weight	4 Kg 9 lbs May vary, depending on configuration)
Size	19" 2U industry standard rack-mountable chassis
Dimensions	44 x 36.3 x 9 cm (17.3 x 14.3 x 3.5")

Specifications may change without prior notice.