



DuraFon PSL-BU

Long-Range Industrial Cordless Phone System Base Unit

The DuraFon PSL-BU is a single-line base for the DuraFon PRO system. It is an ideal solution when there is a need for an additional line or port to be added to the DuraFon PRO system. The DuraFon PSL base unit provides the same long-range coverage as the DuraFon PRO system to allow users to enjoy having telephone access throughout a large, demanding environment.

As an expansion base for the PRO system the PSL can work behind a standard phone line, or analog ports from a PBX or IP-PBX. As part of the DuraFon PRO system, the DuraFon PSL can be part of an up to eight base unit system and support up to 90 handsets. It also is compatible with the DuraFon PRO, DuraWalkie and DuraFon UHF handsets.

Users may include:

- Retail Stores°
- Warehouses / Manufacturing facilities
- Hotels / Motels
- Theaters
- Equipment yards



Key Features

- Digital, long-range cordless base station
- Long-range coverage
- 1-line/port
- Multi-base capacity w/ DuraFon PRO
- 900MHz ISM band
- Optional external indoor / outdoor antenna
- Compatible handsets: DuraFon PRO, DuraWalkie & DuraFon UHF

Detail Features

- Long range: up to:
 - 12 floors in building penetration (office / motel)
 - 250,000 sq. ft. (warehouse / retail store)
 - 3,000 acres (farm / ranch)
- Frequency band: 902~928MHz
- Single line/port base of DuraFon PRO
- Multi-base (Up to 8 bases)
- Multi-handset (Up to 90 handsets)
- Intercom: Not available from base unit
- Broadcasting: Not available from base unit
- Works on analog CO lines or behind PBX analog ports
- Audio-in jack for music/sales message on hold
- Frequency hopping security: 100 times per second
- Digital spread spectrum (DSS) technology for privacy and clarity
- Optional indoor / outdoor antenna – sold separately
- One year limited warranty
- FCC/IC compliant

Technical Specifications

Frequency	Antenna Gain	Voice Quality	Regulation Compliance
902-928 MHz	2 dBi 5dBi External (optional)	TIA/EIA-470B	FCC Part 15, Part 68
RF Power	TX Power	No. of System ID	Operating Temperature
Peak: 708 mW ; Average: 304 mW	708mW	65,535	0~50C
Channel Spacing	Telephone Interface	Ring Signal	Storage Temperature
400 kHz	RJ11x1	20-50 Hz, 12-90 Vrms	-10~70C
Modulation	Speech Coding	Auto-Attendant Coding	Humidity
MSK	8 kbps G.729A	8 kbps G.729	20~75%
Multiple Access	Channel Coding	Flash Time	Storage Temperature
Frequency Hopping TDMA	8 kbps Convolutional + CRC	100-900 ms programmable	-10~70C
Frequency Hopping Rate	Transmission Data Rate	Power Source	Humidity
100 per second	170.678 kbps	100~240V/12V AC/DC Adapter	20~75%
TDMA Frame Length	User Data Rate	Charger Current	Dimension Without Antenna
10 ms	128 kbps duplex	NA	161W x42D x 188H (mm)
Number of Slots/Frame	Duplex	Charge Time	Weight
8	Time Division Duplex (TDD)	NA	424g

Physical Interface

