Poly Studio X50 All-In-One Video Bar with TC8 Controller Kit



*Product image may differ from actual product

Poly DirectorAl

Give everyone in hybrid meetings an equal seat at the virtual table using a choice of framing modes with Poly DirectorAl smart camera technology.

4K camera

No one looks their best with pixilated video. Enjoy richer, more life-like meeting experiences with 4K Ultra/HD video.

Noise blocking innovations

Outside noise and side conversations can quickly derail a hybrid meeting. Keep background noise in check with Poly NoiseBlockAl and Acoustic Fence technologies.

Beamforming microphone

 $Make communicating \ effortless \ for \ everyone \ on \ the \ call, with \ a \ next-generation \ beamforming \ microphone \ array \ that \ clearly \ picks \ up \ all \ voices \ in \ a \ room.$

Datasheet



Poly Studio X50 All-In-One Video Bar with TC8 Controller Kit

Specifications







Camera

Camera resolution: 2160p, 4K UHD (3840 x 2160)

Diagonal field of view (dFoV): 121° Zoom capability: 5x digital Camera type: Single-lens

People video resolution: 4K, 30 fps (TX and RX) from 2048 Kbps; 1080p, 60 fps from 1740 Kbps; 1080p, 30 fps from 1024 Kbps: 720p. 60 fps from 832 Kbps: 720p. 30 fps from 512 Kbps

 $\textbf{Content video resolution (input):} \ \ \textbf{UHD (3840 \times 2160);} \ \ \textbf{HD (1920 \times 1080);} \ \ \textbf{WSXGA+ (1680 \times 1050);} \ \ \textbf{UXGA+ (1680 \times 105$ (1600 x 1200); SXGA (1280 x 1024); WXGA (1280 x 768); HD (1280 x 720); XGA (1024 x 768); SVGA (800 x 600)

Content video resolution (output): UHD (3840 x 2160); WUXGA (1920 x 1200); HD (1920 x 1080); WSXGA+ (1680 x 1050); SXGA+ (1400 x 1050); SXGA (1280 x 1024); HD (1280 x 720); XGA (1024 x 768)

Content sharing: Apple AirPlay; Miracast; Digital Whiteboarding; HDMI input

Video frame rate: 5-60 fps (up to 4K resolution at 15 fps in call)

Digital signage: Appspace; Raydiant Lens privacy capabilities: Attachable Horizontal field of view (hFoV): 110°

Video standards: H.264 AVC; H.264 High Profile; H.265; H.239

Connectivity and communications

Bluetooth version: 5.0 External I/O ports:

1USB Type-C[®] 5Gbps signaling rate 2 USB Type-A 5Gbps signaling rate

1 audio-in

1 audio-out

1 HDMI-in 1.4 (video and audio)

2 HDMI-out 1.4 (video)

1 line in (optional microphone)

Interoperability: Zoom Certified; Microsoft Teams Certified; All cloud service providers through Poly Video App mode; USB Device mode; Support for native 3rd party applications including Zoom,

Microsoft Teams, BlueJeans, Dialpad, GoToRoom, RingCentral and StarLeaf

Wireless technologies:

Wi-Fi 802:11a/b/g/n/ac (MIMO) Multi-channel Concurrency; Bluetooth® 5.01 Not available on no radio versions.

Audio

Audio features:

Poly NoiseBlockAl technology

Poly Acoustic Fence technology

Microphone type: Three MEMS microphones; Two second-order microphones

Speaker output power: 1x 20 W (RMS); 1x 40 W (maximum)

 $\textbf{Audio standards:}\ 22\ \text{kHz with Polycom Siren}\ 22\ \text{technology;}\ 20\ \text{kHz with G.719 (M-Mode)}\ \text{and Polycom}\$ Siren 22 technology; 14 kHz with Polycom Siren 14 technology, G.722.1 Annex C; 7 kHz with G.722, G.722.1;

3.4 kHz with G.711, G.728, G.729A Speaker type: Stereo speakers Sensitivity (speaker): 86.1 dB

Microphone pickup range (metric): Up to 7.62 m Microphone pickup range (imperial): Up to 25 ft

Battery

Power supply type: External Power features:65 BTU h

Certifications

Certified collaboration software: Zoom; Microsoft Teams; Google Meet

Special features: Automatic meeting experience powered by Poly DirectorAl smart camera $technology\ including\ group\ framing, people\ framing\ (preview\ feature), and\ speaker\ framing; Auto$ sensing power supply

Environmental

Operating Altitude (imperial) / Operating Altitude (metric): $16,000\,\mathrm{ft}$ / $4,877\,\mathrm{m}$

Operating humidity range: 15 to 80% Non-operating humidity range: 5 to 95%

Operating Temperature Range (Celsius) / Operating Temperature Range (Fahrenheit): 0 to 40 °C / 32 to

Non-operating temperature - Celsius: -40 to 70 °C Non-operating temperature - fahrenheit: -40 to 158 °F

Applications supported

Management software:

Poly Lens

Security

Standard Kensington lock slot

Weight and dimensions

UPC number: 197497448870 Product number: 83Z47AA

Warranty

Poly standard one-year limited warranty

What is in the box

AC power adapter

Ethernet cable HDMI cable

Privacy cover

TC8 controller

Poly Studio X50

Wall mount kit

Technical Specifications Footnotes