

# **Fanvil V62 Pro Prime Business Phone**

Fanvil V62 Pro is a refined, high-performance prime business phone. It features a 2.8-inch (320x240) HD color LCD screen, supports 12 SIP lines, and 6-way audio conference. With rich functions such as HD audio, dual Gigabit ports, and integrated PoE, and matches with Bluetooth wireless handset, which can meet different enterprise application scenarios and provide users with excellent interactive experience and comfortable instant messaging services.

## **High**lights

- ☑ Support audio code G.722 and Opus, HD audio on speakerphone and handset
- ☑ Support 6-way Audio Conference
- ☐ Fast Ethernet 10/100/1000 Mbps Ethernet, integrated PoE
- ▼ Bluetooth wireless handset provides an excellent audio experience for instantly connected, open workspaces

- ☐ Up to 21 DSS keys, every DSS key can be set as Line/BLF/ Speed Dial Key



























## Generic

- 2.8-inch (320x240) color screen
- 12 SIP lines
- HD voice
- PoE enabled
- Intelligent DSS keysHandset / hands-free / headset mode
- Desktop Stand / Wall-mounted (optional)
- Optional external power supply
- Hall-effect sensor switch handset
- Bluetooth wireless handset

## **Phone Features**

- Local Phonebook (1000 entries)
- Remote Phonebook (XML/LDAP)
- Call logs (In/out/missed, 1000 entries)
- Blocked List/Allowed List
- Screen saver
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronization
- Support Poly wireless headset (Through Poly APD-80 EHS Cable)
- Support Jabra wireless headset (Through Fanvil EHS20 EHS Cable)
- Support Recording(through server)
- Action URL / Active URI
- uaCSTA
- Dial Plan
- SIP Hotspot

- Personalized ringtone settings
- Multicast
- Action Plan
- Group listening

# **Call** Features

- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forwarding (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- DIE
- Call Parking/Pick-up (Depending on server)
- Redial
- Do-Not-Disturb
- Auto-Answering
- Voice Message (With server)
- 6-way Audio Conference
- Hot Line
- Call back
- IP direct dial
- Hot Desking

#### **Audio**

- HD Voice Microphone/Speaker (Handset/Hands-free, 0 ~ 7KHz Frequency Response)
- HAC handset
- Wideband ADC/DAC 16KHz Sampling
- Narrowband Codec: G.711a/u, G.723.1, G.726, G.729, G.729A, G.729B, G.729AB, iLBC
- Wideband Codec: G.722, Opus
- Full-duplex Acoustic Echo Canceller (AEC)
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR) / Automatic Gain Control (AGC)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer
- DTMF: In-band, Out-of-Band (RFC2833/ SIP INFO)
- VQM voice quality monitoring

#### Network

- Physical: 10/100/100 Mbps Ethernet, dual bridged port for PC hypass
- IP Mode:IPv4/IPv6/IPv4&IPv6
- IP Configuration: Static IP / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: L2TP / OpenVPN
- VLAN
- LLDP
- CDP
- OoS
- Support SIP backup server
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)

#### **Protocols**

- SIP2.0 over UDP/TCP/TLS
- DNS A/SRV/NAPTR
- RTP/RTCP/SRTP
- STUN
- DHCP
- CDPLLDP
- PPPoE
- 802.1x
- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069
- AES128 & AES256

#### **Deployment & Management**

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069
- Web Management Portal
- Web-based Packet Dump
- Configuration Export / Import
- Phonebook Import/Export
- Firmware Upgrade
- Syslog

#### **Physical Specifications**

- LCD:2.8-inch (320x240) color screen
- Keypad: 39 keys, including
  - > 7 DSS keys + 1 page key (with LED)
  - > 5 Function keys (Contact, MWI, Mute, Headset, Redial)
  - 4 Soft-keys
  - 4 Navigation keys, 1 OK key
  - > 1 Return key, 1 Home key
  - > 12 Standard Phone Digits keys
  - 2 Volume Control keys, Up/Down
  - 1 Hands-free key
- Bluetooth wireless handset x1
- 1.5M CAT5.E Ethernet Cable x1
- Desk Stand x1
- Status Indicator Light x1 (Red)
- Bluetooth wireless handset status indicator x1 (red, green, and blue)
- RJ9 Port x2: Handset x1, Headset x1
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- Security Slot x1
- Power: DC5V/2A or PoE
- Power Consumption(Adapter): 1.35~4.40W
- Power Consumption(PoE): 1.89~5.60W
- Working Temperature: 0~45 °C
- Working Humidity: 10~95%
- Installation:
  - Desktop Stand
  - Wall-mounted (optional)
- Color: Dark Gray
- Qtv/CTN: 10pcs
- N.W/CTN: 9.50 kg
- G.W/CTN: 10.20 kg
  - Device Dimensions:
  - $\blacktriangleright~$  Desktop Stand (40  $^\circ~$  ): 191.80 x 164.50 x 174.20 mm
  - Desktop Stand (45°): 191.80 x 154.50 x 181.90 mm
  - > Wall mountable: 191.80 x 91.60 x 215.6 mm
- Gift Box Dimensions: 295 x 222 x 56 mm
- Outer CTN Dimensions: 464x305x315mm(10 PCS)

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products. For more information, please visit: www.fanvil.com

